

Calmark offers the C120 snap-in plastic Card Guide with conductive material. This new Card Guide will help protect static sensitive components on the PC board against costly damage from Electro Static Discharge.

FEATURES:

- *Molded with conductive material.*
- *Provides surface resistivity of 10^5 OHM².*
- *Available for 1/16" (1.6) and 3/32" (2.4) thick PC boards.*
- *Wide lead-in for easy card entry.*
- *No mounting hardware required.*
- *Narrow profile for excellent airflow.*
- *Mid-span mounting point for greater stability.*



MATERIAL: 10% Graphite Filled Polycarbonate.
Meets UL94V-2.
Surface Resistivity of 10^5 OHM²

COLOR: Standard color is Black.

TOLERANCES: .xxx = +/- .010, .xx = +/- .02
(.xx = +/- 0.25, .x = +/- 0.5)

INSTALLATION DATA:

Mounting holes .126 +.001/-0.003 dia. hole (front)
(3.20 + 0.03/- 0.08)
.120 +/- .005 x .218 slot (rear & center) (3.05 +/- 0.13)
Installation - Snap-in with sharp impact.
No special installation tools required.

Fits up to .075 (1.91) thick material.

TABULATION

Part No.	L Dim	A Dim	B Dim	C Dim
C120-400	4.02 (102.1)	3.52 (89.4)	---	.076 (1.93)
C120-400-3	4.02 (102.1)	3.52 (89.4)	---	.106 (2.69)
C120-600	6.03 (153.2)	5.53 (140.5)	---	.076 (1.93)
C120-600-3	6.03 (153.2)	5.53 (140.5)	---	.106 (2.69)
C120-700	7.04 (178.8)	6.53 (165.9)	3.26 (82.8)	.076 (1.93)
C120-700-3	7.04 (178.8)	6.53 (165.9)	3.26 (82.8)	.106 (2.69)
C120-700X	7.04 (178.8)	6.53 (165.9)	---	.076 (1.93)
C120-700X-3	7.04 (178.8)	6.53 (165.9)	---	.106 (2.69)
C120-850	8.54 (216.9)	8.04 (204.2)	4.02 (102.1)	.076 (1.93)
C120-850-3	8.54 (216.9)	8.04 (204.2)	4.02 (102.1)	.106 (2.69)
C120-850X	8.54 (216.9)	8.04 (204.2)	---	.076 (1.93)
C120-850X-3	8.54 (216.9)	8.04 (204.2)	---	.106 (2.69)

